


2/186 Dalarna


An abstract pattern with a flame-like texture. The façade appears playful and wild.

Dimensions

Series	Uses	Dimensions (mm)	Ordernumber
C	100	▲ 6900 × ► 3400	C2186
F	50	▲ 6000 × ► 1000	F2186
T	10	▲ 6000 × ► 1000	T2186


100
100-timer formliners are supplied in an individual dimension within the maximum indicated sizes.

50/10
The specified widths of the 10-timer and 50-timer formliners are a fixed dimension and ensure the continuity of the structure in the case of linear patterns. The longitudinal direction of the pattern is variable and can be ordered from 1 m up to the maximum dimension in 10 cm steps.




Section Drawing

The drawing illustrates the cross-section of our formliner.



Profile Continuity

No seamless profile continuity.



Important note: To guarantee homogeneity of the concrete surface, it is not recommended to mix the series.

Material

MATERIAL	RECKLI PUR-Elastomer
TEMPERATURE LIMIT	max. 65 °C
WEIGHT	≈ 27 kg/m²
DIMENSIONAL TOLERANCES	See Formliner Properties page for details

Contact

Are you an architect, planner or user looking for information materials or personal contact? Would you like to order a sample? We will be happy to respond to your individual inquiry.

info@reckli.com
+49 2323 1706-0

RECKLI GmbH
Industriestraße 36
44628 Herne
Germany